



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04Q 7/20	A1	(11) International Publication Number: WO 00/27143
		(43) International Publication Date: 11 May 2000 (11.05.00)

(21) International Application Number: PCT/US99/25838

(22) International Filing Date: 3 November 1999 (03.11.99)

(30) Priority Data:
60/106,816 3 November 1998 (03.11.98) US
09/396,235 15 September 1999 (15.09.99) US

(71) Applicant: SIGNALSOFT CORPORATION [US/US]; 1495 Canyon Boulevard, Boulder, CO 80302 (US).

(72) Inventors: FITCH, James; 827 Walnut Street, Edmonds, WA 98020 (US). HOSE, David, L.; 7358 Park Circle, Boulder, CO 80301 (US). MC KNIGHT, Michael; 9762 Kipling Street, Broomfield, CO 80021 (US).


(74) Agent: FISCHMANN, Kent A.; Holme Roberts & Owen LLP, Suite 4100, 1700 Lincoln Street, Denver, CO 80203-4541 (US).

(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(54) Title: MULTIPLE INPUT DATA MANAGEMENT FOR WIRELESS LOCATION-BASED APPLICATIONS



(57) Abstract.

Multiple location finding equipment (LFE) inputs are used to enhance the location information made available to wireless location-based applications. In one implementation, the invention is implemented in a wireless network including an MSC (112) for use in routing communications to or from wireless stations (102), a network platform (114) associated with the MSC (112), and a variety of LFE systems (104, 106, 108 and 110). A Location Finding System (LFS) (116) in accordance with the present invention is resident on the platform (114). The LFS (116) receives location information from the LFEs (104, 106, 108 and 110) and provides location information to wireless location based applications (118). In this regard, the LFS (116) can receive input information at varying time intervals of varying accuracies and in various formats, and can provide standardized outputs to the applications (118), for example, depending on the needs of the applications (118). Multiple inputs may also be co-processed for enhanced accuracy.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

MULTIPLE INPUT DATA MANAGEMENT FOR WIRELESS LOCATION-BASED APPLICATIONS

FIELD OF THE INVENTION

The present invention relates in general to wireless location-based applications and, in particular, to a method and apparatus for use in processing multiple location finding equipment inputs and making the resulting location information available to wireless location-based applications.

BACKGROUND OF THE INVENTION

Wireless communications networks generally allow for voice and/or data communication between wireless stations, e.g., wireless telephones (analog, digital cellular and PCS), pagers or data terminals that communicate using RF signals. In recent years, a number of location-based service systems have been implemented or proposed for wireless networks. Such systems generally involve determining location information for a wireless station and processing the location information to provide an output desired for a particular application.

Examples of such existing or proposed applications include emergency or "911" applications, location dependent call billing, cell-to-cell handoff and vehicle tracking. In 911 applications, the location of a wireless station is determined when the station is used to place an emergency call. The location is then transmitted to a local emergency dispatcher to assist in responding to the call. In typical location dependent call billing applications, the location of a wireless station is determined, for example, upon placing or receiving a call. This location is then transmitted to a billing system that determines an appropriate billing value based on the location of the wireless station. In handoff applications, wireless location is determined in order to coordinate handoff of call handling between network cells. Vehicle tracking applications are used, for example, to track the location of stolen vehicles. In this regard, the location of a car phone or the like in a stolen vehicle can be transmitted to the appropriate authorities to assist in recovering the vehicle.

From the foregoing, it will be appreciated that location-based service systems involve location finding equipment (LFE) and location-related applications. To some extent, the LFEs and applications have developed independently. In this regard, a number of types of LFEs exist and/or are in development. These include so-called angle of arrival

(AOA) time difference of arrival (TDOA), handset global positioning system (GPS) and the use of cell/sector location. The types of equipment employed and the nature of the information received from such equipment vary in a number of ways. First, some of these equipment types, like GPS, are wireless station-based whereas others are "ground-based", usually infrastructure-based. Some can determine a wireless station's location at any time via a polling process, some require that the station be transmitting on the reverse traffic channel (voice channel), and others can only determine location at call origination, termination, and perhaps registration. Moreover, the accuracy with which location can be determined varies significantly from case to case. Accordingly, the outputs from the various LFE's vary in a number of ways including data format, accuracy and timeliness.

The nature of the information desired for particular applications also varies. For example, for certain applications such as 911, accuracy and timeliness are important. For the applications such as vehicle tracking, continuous or frequent monitoring independent of call placement is a significant consideration. For other applications, such as call billing, location determination at call initiation and call termination or during handoff is generally sufficient.

Heretofore, developers have generally attempted to match available LFEs to particular applications in order to obtain the location information required by the application. This has not always resulted in the best use of available LFE resources for particular applications. Moreover, applications designed to work with a particular LFE can be disabled when information from that LFE is unavailable, e.g., due to limited coverage areas, malfunctions or local conditions interfering with a particular LFE modality. In addition, the conventional query and response mode of operation between applications and the associated LFEs has resulted in the use by applications of LFE dependent data formats, LFE limited data contents, and single LFE input location determinations.

SUMMARY OF THE INVENTION

The present invention is directed to a method and apparatus for using multiple LFE inputs to enhance the location information made available to wireless location-based applications. The invention allows wireless location-based applications access to information based inputs from LFEs of different types, thereby enhancing the timeliness, accuracy and/or reliability of the requested location information. Moreover, in

accordance with the present invention, applications are independent of particular LFEs and can access location information from various LFE sources without requiring specific adaptations, data formats, or indeed knowledge of the LFE sources employed, in order to access and use such location information. By virtue of such independence, new
5 location finding technologies can be readily deployed and existing applications can exploit such new technologies without compatibility issues. The invention also allows multiple LFE inputs, from one or more LFEs, to be used to allow for wireless station tracking and reduced location uncertainty.

According to one aspect of the present invention, a method is provided for using
10 multiple (i.e., two or more) LFEs to support a wireless location application. The method involves receiving first and second inputs from first and second LFEs, storing location information based on the inputs in memory, receiving a location request regarding a wireless station from a wireless location application, selectively retrieving the location information from memory, and outputting a response to the location request to wireless
15 location application.

The first and second LFEs preferably may employ different location finding technologies, e.g., GPS, AOA, TDOA, and cell/sector technologies. The stored location information preferably includes at least location information and corresponding time information for particular wireless stations, and may further include location uncertainty
20 information, travel speed information and travel direction information. In response to the location request from the wireless location application, location information may be retrieved from memory or, alternatively, one or more of the LFEs may be prompted to obtain location information. In this regard, the location request may include a specification regarding the desired location information, for example, indicating how
25 recent or how accurate the information should be. If the memory includes information conforming to the specification, then such information is retrieved and output to the requesting application. Otherwise, appropriate information may be obtained by prompting one or more LFEs to locate the wireless station of interest.

In accordance with another aspect of the present invention, a processing system
30 is interposed between the LFEs and the wireless location applications such that the applications can access location information in a manner that is independent of the location finding technology employed by the LFEs. The corresponding process implemented by the processing system involves: receiving LFE dependent location data

(i.e., location data having a content and/or format dependent on the location finding technology employed) from multiple LFEs receiving a location request from a wireless location application seeking LFE independent location data (i.e., location data having a content and format independent of any particular location finding technology) and responding to the location request based on LFE dependent location data. The process implemented by the processing system may further involve generating and storing LFE independent location data based on the LFE dependent data. The processing system may be resident on the location finding controllers associated with each LFE, on a separate platform and/or the processing system functionality may be distributed over multiple platforms.

According to a still further aspect of the present invention, multiple LFE inputs, are utilized to make a location determination regarding a wireless station. The corresponding method involves the steps of receiving a first location input from a first LFE including first location information and first uncertainty information, receiving a second location input from a second LFE including second location information and second uncertainty information and combining the first and second location inputs to provide a combined location input including combined location information and uncertainty information based on the first and second inputs. Preferably, the first and second inputs include raw location and uncertainty information obtained from LFE measurements prior to aggregation and related processing. One or both of the first and second inputs may constitute partial information, insufficient on its own to yield a location and uncertainty regarding the wireless station within the requirements of the wireless location application. For example, in the case of LFEs that determine location based on readings obtained relative to two or more cell sites, a reading from one of the cell sites may be used in conjunction with other location information, e.g., cell sector information, to make a location determination.

According to another aspect of the present invention, multiple LFE inputs, obtained at different times from the same or different LFEs, are utilized to derive tracking information such as for obtaining improved location determination accuracy. The associated method includes the steps of receiving a first LFE input including first location information and first corresponding time information for a particular wireless station, receiving a second LFE input including second location information and second time information for the wireless station, and using the first and second inputs to derive

tracking information for the wireless station. The tracking information preferably includes information regarding the mobile station's speed of travel and direction of travel. This tracking information can be used in conjunction with subsequent LFE inputs for the wireless station to improve location determination accuracy and can also be used to
5 interpolate wireless station location between location determinations, or to project future wireless station locations as may be desired for some applications. It will be appreciated that this tracking function and other functions are facilitated by the provision of a system for receiving inputs from one or more LFEs, standardizing such inputs with regard to data content and format, and storing such information. In particular, such standardized and
10 stored information can be readily analyzed to yield derivative information regarding wireless station position as well as statistical information for wireless stations of interest in the service area.

A system constructed in accordance with the present invention includes an input facility for receiving inputs from multiple LFEs, a memory such as a cache for storing
15 information from the LFE inputs (e.g., a wireless station identification, a location, a time associated with that location, an uncertainty for that location, and travel speed and bearing), an interface for receiving location requests from wireless location applications and providing responses to such requests, and a processing subsystem for processing the LFE inputs and location requests. The apparatus may also include a facility for
20 prompting LFEs to make location measurements in response to location requests. Among other things, the processing subsystem may convert the LFE inputs into a standard format, direct storage of data in the memory, derive tracking or other derivative information from multiple inputs, analyzing stored information relative to received location requests to determine whether the stored information includes information
25 responsive to the requests and selectively directing the LFEs to make location measurements. The system may be resident on a single or multiple platform and the functionality may be spread among multiple applications.

BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the present invention and further
30 advantages thereof, reference is now made to the following detailed description taken in conjunctions with the drawings in which:

Figure 1 is a schematic diagram of a wireless network implementing a location finding system in accordance with the present invention;

Figure 2 is a schematic diagram illustrating a wireless location-based services system in accordance with the present invention;

5 Figures 3a-3e illustrate various location finding technologies that may be utilized in the context of the present invention;

Figure 4 is a graphical illustration of the use of multiple LFE inputs to reduce location uncertainty in accordance with the present invention;

10 Figure 5 is a graphical depiction of a location uncertainty analysis in accordance with the present invention; and

Figures 6-9 illustrate various wireless location interface signaling sequences in accordance with the present invention.

DETAILED DESCRIPTION

15 In the following description, particular embodiments and implementations of the present invention are set forth in the context of a telecommunications network. It will be appreciated however, that various aspects of the invention are more broadly applicable to other location based services environments.

Referring to Figure 1, an wireless telecommunications network implementing the
20 present invention is generally identified by the reference numeral 100. Generally, the network includes a mobile switching center (MSC) 112 for use in routing wireless communications to or from wireless stations 102, a network platform 114 associated with the MSC 112 for implementing a variety of subscriber or network service functions, and a variety of location finding equipment (LFE) systems 104, 106, 108 and 110. In the
25 illustrated embodiment, the network platform is used to run a Location Manager (LM) 116 in accordance with the present invention and a number of wireless location applications 118. Although the illustrated location finding system 116 and wireless location applications 118 are illustrated as being resident on the network platform 114, it will be appreciated that the elements 116 and 118 may be located elsewhere in the network 100,
30 may be resident on separate platforms, or the functionality of each of these elements 116 and 118 may be spread over multiple platforms. In addition, other applications not depicted in Figure 1 may be resident on the platform 114.

As shown in Figure 1, multiple LFE systems 104, 106, 108 and 110 may be associated with the network 100. These LFE systems 104, 106, 108 and 110 may employ any of a variety of location finding technologies such as AOA, TDOA, GPS and cell/sector technologies and the various system 104, 106, 108 and 110 may be the same as or different from one another. It will be appreciated that the nature of the data obtained from the LFE systems 104, 106, 108 and 110 as well as the path by which the data is transmitted varies depending on the type of LFE employed, and the ability to accommodate a variety of LFEs is an important advantage of the present invention. Some types of LFEs include LFE equipment in the handset. Examples include certain GPS and TDOA systems. In such cases, location information may be encoded into signals transmitted from the handset to a cell site or other receiver, and the information may then be transferred to the platform 114 via the MSC 112 or otherwise. Other LFE systems, i.e., embedded systems use equipment associated with individual cell sites such as specialized antennae to make location determinations such as by triangulation and, again, the resulting location information may be transferred to the platform 114 via the MSC 112 or otherwise. Still other LFE systems employ a network of dedicated LFE equipment that is overlaid relative to the wireless network. Such systems may communicate location information to the platform 114 independent of the MSC 112 and network cell site equipment. In addition, some LFE technologies can be implemented via equipment resident in the handset, in cell sites or other network locations and/or in dedicated LFE sites such that the data pathway of the location information may vary even for a given LFE technology.

Three of the illustrated systems 104, 106 and 108 operate separate from the MSC 112. For example, such systems may include network based systems AOA and TDOA systems and external systems such as GPS. Generally, the illustrated network based system such as AOA and TDOA systems determine the location of a wireless station 102 based on communications between the wireless station and the cell site equipment of multiple cell sites. For example, and as will be described in more detail below, such systems may receive information concerning a directional bearing of the wireless station 102 or a distance of the wireless station 102 relative to each of multiple cell sites. Based on such information, the location of the wireless station 102 can be determined by triangulation or similar geometric/mathematic techniques. External systems such as GPS systems, determine the wireless station location relative to an external system. In the case

of GPS systems, the wireless station 102 is typically provided with a GPS receiver for determining geographic position relative to the GPS satellite constellation. This location information is then transmitted across an air interface to the network 100.

5 The illustrated cell sector system 110 may be associated with cell site equipment for communicating with the wireless station 102. In this regard, the cell site equipment may include three or more directional antennas for communicating with wireless stations within subsections of the cell area. These directional antennas can be used to identify the subsection of a cell where the wireless station 102 is located. In addition, ranging information obtained from signal timing information may be obtained to identify a radius
10 range from the cell site equipment where the wireless station 102 is located, thereby yielding a wireless station location in terms of a range of angles and a range of radii relative to the cell site equipment. This cell/sector location information can be transmitted to the LM 116 via the MSC 112 or possibly via other network information or structure.

15 As shown, the LM 116 receives location information from the various LFE systems 104, 106, 108 and 110. The nature of such information and handling of such information is described in more detail below. Generally, however, such information is processed by the LM 116 to provide location outputs for use by any of various wireless location applications 118 in response to location requests from the application 118. Such
20 applications may include any wireless location services applications such as 911, vehicle tracking and location-based billing programs.

Figure 2 illustrates a location-based services system 200 in accordance with the present invention. An important aspect of the present invention relates to the operation of the LM 214 to receive inputs from multiple LFEs 202, 204 and 206 and provide
25 location outputs to multiple applications 226, 228 and 230. In accordance with the present invention, the LFEs 202, 204 and 206 may be based on different technologies, and may therefore provide different types of location information, in different data formats, with different accuracies based on different signals.

A number of different location finding technologies are depicted in Figures 3a-3d
30 for purposes of illustration. Figure 3a generally shows the coverage area 300 of a cell sector. As noted above, the cell site equipment for a particular cell of a wireless telecommunications system may include a number, e.g., three or more, of directional antennas. Each antenna thus covers an angular range relative to the cell site bounded by

sides 302. In the case of a three sector cell, each antenna may cover about 120° - 150° relative to the cell site. In addition the coverage range for the antenna defines an outer perimeter 304 of the coverage area 300. As shown, the range varies with respect to angle defining a somewhat jagged outer perimeter 304. Accordingly, the actual uncertainty regarding the location of a wireless station located in the illustrated cell sector is defined by the coverage area 300. The location determination output from a cell/sector LFE is therefore effectively defined by the coordinates of the coverage area 300.

Figure 3b depicts a TOA based LFE. In this case, the wireless station's range from a cell sector antenna is determined, based on time of signal arrival or signal transit time to within a radius range, e.g., about 1000 meters. Accordingly, the wireless station's location can be determined to be within an area bounded by sides 306 (based on the angular range of the cell sector antenna) and inner 308 and outer 310 arcs (defined by the ranging uncertainty). The output from a TOA based LFE is effectively defined by the coordinates of the sides 306 and the axes 308 and 310.

An AOA based LFE is generally illustrated in Figure 3c. AOA based LFEs determine the location of a wireless station based on the angle of arrival of signals, generally indicated by rays 312 and 314, from the wireless station as measured by two or more cell sites 316 and 318. Each angle measurement has an angular uncertainty generally indicated by line segments 320 and 322. Consequently, the uncertainty region for a given location determination is defined by a polygon having $2n$ sides, where n is the number of cell sites 316 and 318 involved in the measurement.

Figure 3d illustrates a TDOA based LFE although the illustrated system is cell site based, the TDOA system may alternatively be handset based. In TDOA systems, multiple cell sites measure the time of arrival of signals from a wireless station. Based on such measurements, each cell site can provide information regarding wireless station location in terms of a hyperbola 324 or 326 and an uncertainty, generally indicated by segments 328 and 330. The resulting uncertainty region is defined by a multi-sided region (where each wall is curved) having $2n$ walls, where n is the number of cell sites involved in the determination.

Figure 3e illustrates a GPS based LFE. In GPS systems, the wireless station includes a GPS transceiver for receiving signals indicating the wireless station's location relative to multiple satellites in the GPS constellation. Based on these signals, the geographic coordinates of the wireless station's location is determined to an accuracy of

perhaps 20 meters as generally indicated by circle 332. This information is then transmitted to the wireless network across an air interface.

Referring again to Figure 2, each of the LFEs 202, 204 or 206 outputs location information to its respective LFC 208, 210 or 212. The nature of this "raw" LFE output depends in part on the type of LFE involved. For example, in the case of a cell sector system the output may be a sector identifier or coordinates; in the case of a TOA system, the output may be a sector identifier or coordinates and a radius; in an AOA system the output may be angular measurements and corresponding cell site identifiers/coordinates; in TDOA systems the output may define multiple hyperbolae; and in GPS systems the output may be geographic coordinates.

The LFCs 208, 210 and 212 collect and aggregate the "raw" location into a standard format which is then sent to the location cache (LC) 220 of the LM 214 for storage. Aggregation involves using the raw data to determine a wireless station location and uncertainty. For some LFE systems, such as GPS systems, this process is simple because location coordinates are reported and the uncertainty is known. For other LFE systems, aggregation is more involved. For example, in the case of TDOA, aggregation may involve receiving multiple hyperbola definitions and using these definitions to define a wireless station location and a multi-sided uncertainty region. The LFCs 208, 210 and 212 may be provided by the LFE vendors or their functionality may be incorporated into a subsystem of the LM 214.

In the context of the present invention, it is useful to express the location information in a standard format. Accordingly, the LFCs 208, 210 and 212 or a cooperating subsystem of the LM 214 associated with the LC 220, may implement a conversion facility for converting the determined (processed) location information of the LFCs 208, 210 and 212 into standardized location information expressed, for example, as geographical location coordinates and a region of uncertainty. The uncertainty region may be of any shape (e.g., polygonal) depending, for example, on the nature of the LFE(s) employed. Once such type of uncertainty region is a circular region that can be characterized by an uncertainty radius. In the illustrated embodiment, two dimensional location coordinates are defined (e.g., latitude and longitude) together with an uncertainty radius applied relative to the location coordinates. It will be appreciated that the standard format may allow for altitude coordinates, non-circular uncertainty regions and other parameters.

Referring again to Figures 3a-3e, examples of these coordinates and circular uncertainty regions are graphically depicted. In particular, in each case, a location "L" and standardized uncertainty region "C" are geometrically defined such that the standardized uncertainty region C circumscribes the actual uncertainty region associated with that location finding technology. In this regard, the location L may be defined first (e.g., as the intersection of rays 312 and 314 in Figure 3c) and then the minimum radius circle C may be defined to circumscribe the actual uncertainty region; the standardized uncertainty region C may be defined first (e.g., as the minimum radius circle required to circumscribe the actual uncertainty region) and then L be defined as the center of the circle C; or any other appropriate geometric solutions/approximations may be employed.

This standardized location information is then stored in a database in LC 220. Specifically, the location coordinates for a wireless station and corresponding uncertainties can be stored in a field, in a relational database, or can otherwise be indexed to a wireless station identifier, e.g., a cellular telephone Electronic Serial Number/Mobile Identification Number (ESN/MIN). The coordinates and uncertainty may be expressed in terms of any appropriate units. For example, the coordinates may be expressed as latitude and longitude values in units of 10^{-6} degrees and the uncertainty may be expressed in units of meters.

The stored, standardized information can be used to perform a number of multiple input analyses. Three examples of such facilities are generally indicated by the velocity 216, multi-input processing 217 and tracking 218 facilities of LM 214. The velocity facility 216 involves determining and storing speed information and direction (bearing) information for a wireless station based on multiple LFE inputs for the station. Because of the standardized format, such determinations can be easily made relative to inputs from the same or different LFEs 104, 106 and/or 108. The velocity information can be obtained based on knowledge of the change in position and the change in time (determined by way of the time stamps associated with the location information) and may be expressed in terms of latitudinal and longitudinal velocity components in units of meters per second, together with velocity uncertainty terms. The direction information can be directly obtained from the location information, or can be based on a ratio of the velocity components, using standard trigonometric principles. It will be appreciated that such speed and direction information may be useful for a variety of applications such as vehicle tracking.

The multi-input processing facility 217 can be used to improve location accuracy based on multiple inputs from the same or, more preferably, different LFEs 202, 204 and/or 206. That is, if two locations with two uncertainties can be obtained for a given wireless station at a given time, a reduced uncertainty can be calculated as the overlap of the two original uncertainties. A complicating factor is that the locations and uncertainties stored in the LC 220 for a given wireless station will typically not represent location determinations for the same time. Because wireless stations are generally mobile, an additional element of uncertainty is introduced.

The illustrated multi-input processing facility 217 takes time into account. This is accomplished by:

1. accessing the LC 220 to obtain two (or more) sets of location information for a given wireless station;
2. identifying a location, uncertainty and time for each set of information;
3. determining a time difference between the times of the information sets;
4. calculating an element of location uncertainty associated with the time difference; and
5. applying the calculated element of location uncertainty to the earlier location information to obtain time translated location information.

This time translated location information can then be compared to the later location information in an uncertainty overlap analysis, as described below, to obtain a reduced uncertainty.

Various processes can be employed to calculate the additional, time-related element of location uncertainty. A simple case involves assuming a maximum rate of travel. For example, a maximum rate of travel of 70 miles per hour may be assumed to account for travel of a mobile phone in a vehicle. The uncertainty associated with an earlier location determination may then be expanded by a value determined by multiplying the maximum rate of travel by the time difference between the two measurements to be compared. Different maximum travel rates may be assumed for different conditions, for example, a lower rate may be assumed for city locations than for suburban locations, a lower rate may be assumed for peak traffic periods, or a lower rate may be assumed for mobile stations that are not generally used on fast moving vehicles. Also, wireless station speed and direction information as described above or other

tracking information as described below may be used to reduce the time-related element of uncertainty.

Once such a time translation process has been employed to normalize multiple LFE inputs relative to a given time, an uncertainty overlap analysis can be implemented. Such an analysis is graphically illustrated in Figures 4 and 5. Referring first to Figure 4, the smaller circle represents a location and uncertainty associated with a later LFE input taken to be at time t_1 . The larger circle 402 represents a location and uncertainty associated with a time translated location information based on an earlier LFE input taken to be at time t_0 . Circle 402 is illustrated as having a larger uncertainty than circle 400 to account for the additional time and travel related element of uncertainty associated with the time translation. The shaded overlap area 404 represents the reduced uncertainty achieved by using multiple inputs. That is, statistically, if circle 400 represents a 95% confidence level regarding the position of the station at t_1 and circle 402 represents a nearly 95% confidence level regarding the position of the station at t_1 , the position of the station can be determined to be in the shaded area 404 with a high level of confidence.

Figure 5 illustrates a mathematical process for combining the original uncertainties to obtain a more accurate position and uncertainty. Mathematically, the problem is to compute the intersection of the circular uncertainty regions, and express the result as a location with an uncertainty (e.g., a circular uncertainty circumscribing the intersection region). To simplify the mathematics, the geometric arrangement of Figure 4 is translated to provide a first axis (x in Figure 5) that extends through the centerpoints of the circular uncertainty regions 500 and 502 (generally, the coordinates of the originally determined locations) and an orthogonal axis (y) intersecting the center of the larger (in this case later) circular uncertainty region 502. The mathematical equations for the boundaries of circular uncertainty regions 500 and 502 are:

$$x^2 + y^2 = r_1^2 \quad (1)$$

$$(x - x_0)^2 + y^2 = r_2^2 \quad (2)$$

It will be appreciated that the values of r_1 , r_2 and x_0 are known as these are the uncertainty of the time translated information, the uncertainty of the later LFE input and the difference between r_1 and r_2 , respectively. Equations (1) and (2) can then be

simultaneously solved to obtain x and y , where x is the new location and y is the radius of the new uncertainty region. Finally, these values can be translated back into Earth coordinates. This mathematical analysis can be used for cases where $x \leq x_0$ and $x_0 \leq r_1 + r_2$. In other cases, the most recent or most accurate of the LFE inputs can be utilized.

5 The illustrated LM 214 also includes a tracking facility 218. Such tracking involves using historical information (at least two sets of location information) and using such information to reduce the uncertainty associated with current measurements. That is, by tracking movement of a wireless station, information can be obtained that is useful in analyzing the uncertainty of current measurements. In a simple case, where tracking
10 information indicates that a wireless station is moving in a straight line (or otherwise on a definable course) or at a constant speed, then curve fitting techniques or other simple algorithms can be employed to obtain a degree of confidence concerning current location. Moreover, interpolation and extrapolation techniques can be employed to determine location at times between measurements or in the future. Such information may be useful
15 to determine when a wireless station crossed or will cross a boundary as may be desired, for example, for location-based billing applications or network management applications (for handling hand-off between adjacent cells). It will thus be appreciated that the information stored in the LC 220 may include wireless station identifiers, locations, uncertainties, confidence levels, travel speeds, travel directions, times and other
20 parameters. Data may be purged from the LC upon reaching a certain age in order to remove visitor data and other unnecessary data.

The velocity facility 216, multi-input processing facility 217, and tracking facility 218 may use the raw information data transmitted from the LFEs 202, 204 and 206 to the LFCs 208, 210 and 212 in place of, or in addition to, the LFC outputs. For example, the
25 multi-input processing facility 217 may use a hyperbola definition from a TDOA system in combination with an angle from an AOA system (or other combination of partial LFE outputs) if such combination yields an improved location accuracy or otherwise provides a suitable location determination. Similarly, it may be preferred to use the raw data for velocity or tracking calculations as such data is mathematically closer to the moving
30 wireless station and may more accurately reflect station movement.

Referring again to Figure 2, the illustrated system 200 includes a wireless location interface (WLI) 224 that allows wireless location applications 226, 228 and 230 to selectively access information stored in the LC 220 or prompt one or more of LFEs 202.

204 and/or 206 to initiate a location determination. The WLI 224 provides a standard format for submitting location requests to the LM 214 and receiving responses from the LM 214 independent of the location finding technology(ies) employed. In this manner, the applications can make use of the best or most appropriate location information available originating from any available LFE source without concern for LFE dependent data formats or compatibility issues. Moreover, new location finding technologies can be readily incorporated into the system 200 and used by the applications 226, 228 and 230 without significant accommodations for the existing applications 226, 228 and 230, as long as provision is made for providing data to the LC 220 in the form described above.

10 The WLI 224 of the illustrated implementation allows the applications to include a specification with a location request regarding the desired location information. For example, the specification may include one or more of the following: the timeliness of the location information (e.g., not older than [date stamp parameter]), the accuracy of the information (e.g., uncertainty not exceeding [uncertainty parameters]), confidence
15 (confidence at least equal to [confidence parameter]). Alternatively, the request may specify the use of the most recent available information, most accurate available information, etc. In addition, the location request can specify whether the request is for one-time only location information or ongoing monitoring of a mobile station, whether the LM 214 should wait for the next available update or force a location determination,
20 whether redundant or unnecessary updates should be filtered (e.g., do not send updates more often than once a minute or if wireless station has moved less than 50 meters), and what the priority of the request is. In this manner, ongoing monitoring may be employed, for example, by applications such as vehicle tracking and 911, and event triggered requests can be used for other applications such as location based billing. In each case,
25 the desired location parameters can be specified.

Figures 6-9 show messaging sequences for various location request situations. Specifically, Figure 6 shows a series of messages for a location request where the application waits for the next available location determination. The process is initiated by transmitting a WLARequestedLocationInvoke message from one of the WLAs to the
30 LC. This message may include parameter fields for Wireless Station Identification, WLA Identification, Location Request Filter, Location Request Mode (check LC or force LFE location determination), Geographic Extremes (where to look for wireless station), Request Priority (processing priority relative to other pending requests) and Fallback

Timeout (time that WLA will wait for a current location determination before accepting the information stored in the LC).

In the case of Figure 6, where the WLA waits for the next available location determination, the next message may be a system access or other triggering signal from the wireless station to the LFE. In response, the LFC sends raw location measurement information to the LFE which, in turn, provides a location update to the LC. The LM then responds to the location request from the WLA with a WLARequestLocationReturn Result message. This message may include the following parameters: Geographic Location, Location Uncertainty, Location Determination Technology, Time Stamp, Velocity, Velocity Uncertainty, and Fallback Timeout Occurred Flag.

Figure 7 illustrates a sequence of messages associated with a forced LFE access. The illustrated sequence is initiated by a WLARequestLocationInvoke as described above. In response, the LM transmits a QueryLocationInvoke message to the LFC to force an LFE determination, and the LFC confirms receipt of this message with a QueryLocationReturnResult message. The parameters of the QueryLocationInvoke message may include Wireless Station ID, Geographic Extremes and Measurement Priority (relative to other pending measurement requests). The LFC then sends a One-time Measurement Request message to the LFE to instruct the LFE to obtain location information for the wireless station of interest. In cases where ongoing monitoring is desired, this message may be sent repeatedly or periodically as indicated by multiple arrowheads in the Figure. In order to obtain a location measurement, it is generally necessary to cause the wireless station to transmit an RF signal for detection by the LFE or to communicate location data to the wireless network. This can be achieved by conducting a polling process using an LRF which requests all wireless stations to register. In this regard, the LFC issues a Force System Access message to the LRF which, in turn, transmits the Force System Access message to the wireless station. In response, a system access signal is transmitted by the wireless station and detected by the LFE. The LFE then transmits Location Measurement Information to the LFC. This may be repeated in the case of ongoing monitoring. The LFC provides a Location Update to the LC and, finally, the LM transmits a WLARequestLocationReturnResult as described above to the WLA.

Figure 8 represents the case where a location request can be responded to based on the data stored in the LC. This occurs, for example, where the cached data satisfies

the request specification or the request specifically seeks data from the LC. Very simply, the illustrated message sequence involves transmission of a WLARequestLocationInvoke message from the WLA to the LM and a responsive WLARequestLocationReturnResult. It will be appreciated that this case allows for a very fast response. Moreover, it is anticipated that the cached data will be sufficient in many cases for many WLAs.

Figure 9 shows a typical message sequence for the case where a WLA requests ongoing updates regarding the location of a wireless station. The update period is initiated upon transmission of a WLARequestRegisterInvoke message from the WLA to the LM and receiving a WLARequestRegisterReturnResult in confirmation; and terminates upon transmission of a WLARequestUnregisterInvoke message and receiving a WLARequestUnregisterReturnResult in confirmation. The parameters included in the Register message can include the wireless station ID, update interval, whether wireless station access should be forced, etc. As shown in the Figure, the LM receives Location Updates from time-to-time from the Location Determination Technology (LDT). It will be noted that only those Updates occurring between Registration and Unregistration are communicated to the WLA. In this regard, the Updates are communicated from the LM to the WLA via a LMLocationUpdateInvoke message and a LMLocationUpdateReturnResult is transmitted in confirmation.

The system 200 also includes a Geographic Information System (GIS) based module 222 for use in correlating geographic coordinate information to mapping information, e.g., street addresses, service area grids, city street grids (including one-way or two-way traffic flow information, speed limit information, etc.) or other mapping information. For example, it may be desired to convert the geographic coordinates of a 911 call to a street address for use by a dispatcher, or to correlate a call placement location to a wireless network billing zone. In this regard, the GIS module 222 may communicate with the LFCs 208, 210, and 212, the LFC 214 and/or the WLAs 226, 228 and 230 to correlate location information to GIS information, and to correlate GIS information to application-specific information such as wireless network billing zones. A suitable GIS based module 222 is marketed under the trademark MAPS by SignalSoft Corporation of Boulder, Colorado.

While various embodiments of the present invention have been described in detail, it is apparent that further modifications and adaptations of the invention will occur

to those skilled in the art. However, it is to be expressly understood that such modifications and adaptations are within the spirit and scope of the present invention.

What Is Claimed Is:

1. A method for use in a wireless network to obtain requested location information regarding a wireless station and provide the requested location information to a wireless location application, the wireless network being associated with at least first
5 location finding equipment and second location finding equipment for providing information regarding locations of wireless stations in the network, the method comprising the steps of:

first receiving a location request regarding said wireless station from said wireless location application, said location request seeking said requested location information;
10 storing data in memory relating to said first location input and said second location input;

second receiving a first location input based on first location information provided by said second location finding equipment, and a second location input based on second location information provided by said second location finding equipment;

15 obtaining said requested location information by selectively retrieving data from said memory based on said location request; and

outputting said requested location information to said wireless location application, wherein said wireless location application is supported by said first location finding equipment and said second location finding equipment.

20 2. A method as set forth in Claim 1, wherein said first location finding equipment employs a first location finding technology and said second location finding equipment employs a second location finding technology different than said first location finding technology, and said step of second receiving comprises standardizing information obtained from said first location finding equipment and said second location
25 finding equipment to provide said respective first and second location inputs, wherein said first and second location inputs include location information in a standardized format.

3. A method as set forth in Claim 1, wherein said first location finding equipment employs a first location finding technology and said second location finding
30 equipment employs a second location finding technology different than said first location finding technology, and said step of second receiving comprises providing a first location finding controller associated with said first location finding equipment for receiving first data from said first location finding equipment in a first data format, providing a second

location finding controller associated with said second location finding equipment for receiving second raw data from said second location finding equipment in a second format, and operating said first and second location finding controllers to convert said respective first and second data into standardized location data.

5 4. A method as set forth in Claim 1, wherein said step of storing comprises storing information for individual wireless stations including at least a location and a time.

 5. A method as set forth in Claim 1, wherein said step of storing comprises storing information for individual wireless stations including an uncertainty regarding
10 location.

 6. A method as set forth in Claim 1, wherein said step of storing comprises information for individual wireless stations including one of a travel speed and a travel direction.

 7. A method as set forth in Claim 1, wherein said step of first receiving
15 comprises obtaining information regarding the identity of a wireless station and a specification concerning the requested location information.

 8. A method as set forth in Claim 1, wherein said step of first receiving comprises providing an interface defining a format for receiving location requests and receiving said location request in accordance with the defined format.

20 9. A method as set forth in Claim 1, wherein said step of obtaining comprises identifying a specification of the location request regarding the desired location information and determining whether the stored data includes information conforming to the specification.

 10. A method as set forth in Claim 1, wherein said step of obtaining comprises
25 prompting one of the first location finding equipment and second location finding equipment to obtain location information regarding the wireless station in response to the location request.

 11. A method as set forth in Claim 1, wherein said step of outputting
30 comprises providing an output including at least a wireless station identification and a location of the wireless station.

 12. A method as set forth in Claim 1, wherein said step of outputting comprises providing an output including a time and an uncertainty regarding location.

13. A method as set forth in Claim 1, wherein said step of outputting comprises providing an output including one of a speed of travel and direction of travel for the wireless station.

14. A method as set forth in Claim 1, further comprising combining multiple
5 location finding equipment inputs for the wireless station to make a location determination.

15. A method as set forth in Claim 14, wherein said step of combining comprises obtaining a first set of information including first location information and first time information for said wireless station, obtaining a second set of information including
10 second location information and second time information for said wireless station, determining a time difference between said first and second sets of information, and adjusting one of said first and second sets of information based on said time difference.

16. A method as set forth in Claim 15, wherein said adjusting comprising calculating one of a change in position and an uncertainty in position based on said time
15 difference.

17. A method as set forth in Claim 14, wherein said step of combining comprises obtaining a first set of position information including a position and an uncertainty, obtaining a second set of information including a position and an uncertainty and combining said first set and said second set to yield a third set including a position
20 and an uncertainty for said wireless station, wherein said third set includes a reduced uncertainty relative to said first and second sets.

18. A method as set forth in Claim 14, wherein said first location finding equipment employs a first location finding technology and said second location finding equipment employs a second location finding technology different than said first location
25 finding technology, said first location finding technology involves a first location finding controller for receiving first raw location data from said first location finding equipment and aggregating said first raw data to provide said first location input and said second location finding technology involves a second location finding controller for receiving second raw location data information from said second location finding equipment and
30 aggregating said second raw data to provide said second location input, and said step of combining comprises obtaining said first raw data from said first location finding equipment, obtaining said second raw data from said second location finding equipment,

and said step of combining comprises using one of said first raw data and said second raw data to obtain derived location information.

19. A method as set forth in Claim 1, further comprising the step of obtaining tracking information regarding movement of said wireless station, and using said tracking
5 information to derive location information.

20. A method as set forth in Claim 19, wherein said step of deriving tracking information comprises receiving first location information obtained for a first time and obtaining second location information obtained for a second time and deriving said tracking information based on said first and second location information wherein said
10 tracking information comprises at least one of speed of travel information and direction of travel information.

21. A method for use in a wireless network to obtain requested location information regarding a wireless station and provide the requested location information to a wireless location application, the wireless network being associated with at least first
15 location finding equipment and second location finding equipment for providing information regarding locations of wireless stations in the network, the method comprising the steps of:

receiving a first location input based on first location information provided by said first location finding equipment and a second location input based on second location
20 information provided by said second location finding equipment;

combining said first location input from said first location finding equipment and said second location input from said second location finding equipment; and

outputting said requested location information to said wireless location application based on said step of combining said first location input and said second
25 location input.

22. A method for use in a wireless network to obtain requested location information regarding a wireless station and provide the requested location information to a wireless location application, the wireless network being associated with at least first location finding equipment for providing information regarding locations of wireless
30 stations in said network the method comprising the steps of:

receiving first and second location finding equipment inputs;

obtaining tracking information regarding movement of said wireless station based on said first and second inputs, said tracking information including at least one of speed of travel information and direction of travel information for said wireless station;

5 using said tracking information and a third location finding equipment input to determine a location of said wireless station; and
outputting said location to said wireless location application.

23. A method for use in a wireless network to obtain requested location information regarding a wireless station and provide the requested location information to a wireless location application, the wireless network being associated with location
10 finding equipment for providing information regarding locations of wireless stations in a network service area, the method comprising the steps of:

receiving a plurality of location inputs provided by said location finding equipment, each of said inputs having one of a data structure and a data content dependent on a type of the location finding equipment;

15 receiving a location request from said wireless location application, the location request being in accordance with a standard protocol defining requested location information independent of any particular type of location finding equipment;

storing data in memory relating to said plurality of location inputs;

obtaining said requested location information by selectively retrieving data from
20 said memory based on said location request; and

outputting said requested location information to said wireless location application, wherein wireless location equipment independent information is provided to wireless location applications based on wireless location equipment dependent inputs.

1/8




FIG.1




FIG.2




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 3D




FIG. 3E




FIG. 4




FIG. 5




FIG. 6

6/8




FIG.7

7/8




FIG.8




FIG.9

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US99/25838

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) : H04Q 7/20

US CL : 455/456, 457; 342/357

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 455/422, 456, 457, 517; 342/357, 450, 457

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)
WEST**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5,327,144 A (STILP et al) 05 July 1994 (05.07.1994), column 5 - column 7.	1, 4-17, 19-23
Y	US 5,732,354 A (MACDONALD) 24 March 1998 (24.03.1998), column 6 - column 9.	1, 4-17, 19-23
Y, P	US 5,844,522 A (SHEFFER et al) 01 December 1998 (01.12.1998), entire reference.	1, 4-17, 19-23.
A	US 5,223,844 A (MANSELL et al) 29 June 1993 (29.06.1993), entire reference.	1, 4-17, 19-23
A	US 5,600,706 A (DUNN et al) 04 February 1997 (04.02.1997), entire reference.	1, 4-17, 19-23
A	US 5,835,907 A (NEWMAN) 10 November 1998 (10.11.1998), entire reference.	1, 4-17, 19-23.

☐ Further documents are listed in the continuation of Box C.☐ See patent family annex.

Special categories of cited documents:	
"A" document defining the general state of the art which is not considered to be of particular relevance	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"E" earlier application or patent published on or after the international filing date	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"O" document referring to an oral disclosure, use, exhibition or other means	"&" document member of the same patent family
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

17 DECEMBER 1999

Date of mailing of the international search report

18 JAN 2000

Name and mailing address of the ISA/US

Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703)305-3230

Authorized officer

QUOCHEN VUONG *James R. Matthews*

Telephone No. (703) 306-4530

Form PCT/ISA/210 (second sheet) (July 1998)